# MIDJ



# Calla P L\_N PP Armchair

design Fabrizio Batoni, 2019

Armchair with four-legs wooden base. Polypropylene seat. Optional: fabric, leather or faux leather cushion.

# **Colors and Materials**

#### Structure




Stained ash veneered

#### Coating

Polypropylene

10 Colors

#### **Dimensions**



# **Volumetric Details**

Weight 7 Kg Volume 0.26 mc Package 1

### Downloads

.dwg Calla P L\_N PP (zip) - https://www.midj.com/images/uploads/resources/3d-calla-p-I-n-pp-dwg.zip .dxf Calla P L\_N PP (zip) - https://www.midj.com/images/uploads/resources/3d-calla-p-I-n-pp-dxf.zip .obj Calla P L\_N PP (zip) - https://www.midj.com/images/uploads/resources/3d-calla-p-I-n-pp-obj.zip .fbx Calla P L\_N PP (zip) - https://www.midj.com/images/uploads/resources/3d-calla-p-I-n-pp-fbx.zip .3ds Calla P L\_N PP (zip) - https://www.midj.com/images/uploads/resources/3d-calla-p-I-n-pp-fbx.zip

## **Materials Certifications**

#### Stained ash veneered

Veneered woods are the result of a process of gluing extremely thin sheets of wood applied to various types of supports to produce furnishing elements, which have a similar appearance to solid wood, but with better performance in terms of resistance to woodworms, lightness and greater stability over time. If exposed to light, and in any case with the passage of time, the color of the veneer changes. It may happen that furniture of the same color purchased after some time, show color differences. Upon request, the veneered parts can be supplied with certified origin from forests managed in a correct and responsible manner, according to the rigorous environmental standards established by the FSC circuit.

#### CLEANING AND MAINTENANCE

For ordinary cleaning of veneered woods, use a cloth moistened with neutral soap well diluted in water or specific products. Always dry after each application with a dry cloth or paper towel. Do not use abrasive products. In case of accidental spills of substances or liquids, immediately dab the wood with paper towel or with a dry and clean cloth. Avoid proximity to heat sources. Evenly expose the veneered woods to light, for example by periodically opening the table extensions that are stored inside the structure, or by moving any object placed on the surface, such as vases and accessories.

These tips are cleaning recommendations and do not guarantee complete stain removal. We recommend that you always test the cleaning method on a hidden part of the item to check the resistance of the color.

Colour samples are to be considered approximate for each product. Slight color differences between a lot and the other are to be considered normal.

# **Materials Certifications**

#### Polypropylene

Polypropylene is a resistant, non-toxic, odorless, heat resistant and easy to clean plastic material. It is also suitable for outdoor use. Our polypropylene is a material reinforced with glass fiber: an option with excellent mechanical properties that allows the product to be solid and resistant. This material has a marked resistance to fading: a treatment with UV stabilizer and AS antistatic protection works to prolong the beauty of the product by slowing the fading process. However, by exposing the chair to the sun and atmospheric agents for very long periods, the color can undergo alterations. As a thermoplastic material, it is 100% recyclable.

#### CLEANING AND MAINTENANCE

Polypropylene seats are easy to clean, and do not require the use of specific products, except in the case of stubborn and hard to remove stains. For simple and effective cleaning, use a microfiber cloth soaked in water or a solution of water and neutral soap. In case of stubborn stains, it is possible to act directly on them with a neutral detergent, always with the help of a microfiber cloth. Then rinse with water. Avoid abrasive sponges, stain removers and granular cleaners that could scratch the surface. If using a chlorine-based cleaner, rinse and do not dry in direct sunlight.

These tips are cleaning recommendations and do not guarantee complete stain removal. We recommend that you always test the cleaning method on a hidden part of the item to check the resistance of the material.