



# Joe H65 / H75 M LG Stool

design Midj R&D, 2015

Stool with four legs base in lacquered steel. Wooden seat and backrest.

## Colors and Materials

### Structure



Papaya orange steel



Light blue metal



White steel



Bronze metal



Ash grey metal



Sand steel



Fango steel



Golden yellow metal




Pastel yellow steel



Grafite metal



Light grey steel



Brown steel



Black steel



Ocher steel



Facepowder pink metal



Red steel



Bulgaro red metal




Cherry red metal



Pine green steel




Sage green metal




Dark green metal

### Coating




**Stained ash veneered**

10 Colors



**Veneered flamed walnut**

## Dimensions



	A (cm) (inch)	B (cm) (inch)	C (cm) (inch)	
<b>H65 (cm)</b> (inch)	98 38.6	44 17.3	52 20.5	66 26
<b>H75 (cm)</b> (inch)	108 42.5	44 17.3	52 20.5	76 29.9

## Volumetric Details

**Weight** 7.5 Kg  
**Volume** 0.30 mc  
**Package** 1

## Downloads

- [.3ds Joe H65 M LG \(zip\)](https://www.midj.com/images/uploads/resources/3d-midj-joe-h65-m-lg-3ds.zip) - <https://www.midj.com/images/uploads/resources/3d-midj-joe-h65-m-lg-3ds.zip>
- [.dae Joe H65 M LG \(zip\)](https://www.midj.com/images/uploads/resources/3d-midj-joe-h65-m-lg-dae.zip) - <https://www.midj.com/images/uploads/resources/3d-midj-joe-h65-m-lg-dae.zip>
- [.dxf Joe H65 M LG \(zip\)](https://www.midj.com/images/uploads/resources/3d-midj-joe-h65-m-lg-dxf.zip) - <https://www.midj.com/images/uploads/resources/3d-midj-joe-h65-m-lg-dxf.zip>
- [.obj Joe H65 M LG \(zip\)](https://www.midj.com/images/uploads/resources/3d-midj-joe-h65-m-lg-obj.zip) - <https://www.midj.com/images/uploads/resources/3d-midj-joe-h65-m-lg-obj.zip>
- [.stl Joe H65 M LG \(zip\)](https://www.midj.com/images/uploads/resources/3d-midj-joe-h65-m-lg-stl.zip) - <https://www.midj.com/images/uploads/resources/3d-midj-joe-h65-m-lg-stl.zip>
- [.3ds Joe H75 M LG \(zip\)](https://www.midj.com/images/uploads/resources/3d-midj-joe-h75-m-lg-3ds.zip) - <https://www.midj.com/images/uploads/resources/3d-midj-joe-h75-m-lg-3ds.zip>
- [.dae Joe H75 M LG \(zip\)](https://www.midj.com/images/uploads/resources/3d-midj-joe-h75-m-lg-dae.zip) - <https://www.midj.com/images/uploads/resources/3d-midj-joe-h75-m-lg-dae.zip>
- [.dxf Joe H75 M LG \(zip\)](https://www.midj.com/images/uploads/resources/3d-midj-joe-h75-m-lg-dxf.zip) - <https://www.midj.com/images/uploads/resources/3d-midj-joe-h75-m-lg-dxf.zip>
- [.obj Joe H75 M LG \(zip\)](https://www.midj.com/images/uploads/resources/3d-midj-joe-h75-m-lg-obj.zip) - <https://www.midj.com/images/uploads/resources/3d-midj-joe-h75-m-lg-obj.zip>
- [.stl Joe H75 M LG \(zip\)](https://www.midj.com/images/uploads/resources/3d-midj-joe-h75-m-lg-stl.zip) - <https://www.midj.com/images/uploads/resources/3d-midj-joe-h75-m-lg-stl.zip>

## Materials Certifications

### Dark green metal

The technologies used in the previous phase of powder coating play a fundamental role in the final result of the processing. They are in fact essential to increase adherence paint on the metal surface and then guarantee its duration over time. The metal frames, following a total cleaning of the surface, pass through chemical conversion processes, creating a compact base that allows for better adhesion of the subsequent treatment. In the last phase the object subjected to the powder coating process is placed in a polymerization oven, going to form an adherent and extremely tight layer durable. This particular paint job is ideal for outdoor use.

To clean the surface, use a damp microfiber cloth with neutral soap or specific metal cleaning products. Avoid hitting or rubbing the surface with sharp objects. Do not use scourers or other abrasive materials, since they would inevitably scratch the surface. Do not leave rusty iron objects on the surface for too long.

These surface treatments are not suitable for outdoor use, but they guarantee excellent resistance to frequent use, dirt and dust.

## Materials Certifications

## Stained ash veneered

Veneered woods are the result of a process of gluing extremely thin sheets of wood applied to various types of supports to produce furnishing elements, which have a similar appearance to solid wood, but with better performance in terms of resistance to woodworms, lightness and greater stability over time. If exposed to light, and in any case with the passage of time, the color of the veneer changes. It may happen that furniture of the same color purchased after some time, show color differences. Upon request, the veneered parts can be supplied with certified origin from forests managed in a correct and responsible manner, according to the rigorous environmental standards established by the FSC circuit.

### CLEANING AND MAINTENANCE

For ordinary cleaning of veneered woods, use a cloth moistened with neutral soap well diluted in water or specific products. Always dry after each application with a dry cloth or paper towel. Do not use abrasive products. In case of accidental spills of substances or liquids, immediately dab the wood with paper towel or with a dry and clean cloth. Avoid proximity to heat sources. Evenly expose the veneered woods to light, for example by periodically opening the table extensions that are stored inside the structure, or by moving any object placed on the surface, such as vases and accessories.

These tips are cleaning recommendations and do not guarantee complete stain removal.

We recommend that you always test the cleaning method on a hidden part of the item to check the resistance of the color.

Colour samples are to be considered approximate for each product. Slight color differences between a lot and the other are to be considered normal.

---

## Materials Certifications

### Veneered flamed walnut

Veneered woods are the result of a process of gluing extremely thin sheets of wood applied to various types of supports to produce furnishing elements, which have a similar appearance to solid wood, but with better performance in terms of resistance to woodworms, lightness and greater stability over time. If exposed to light, and in any case with the passage of time, the color of the veneer changes. It may happen that furniture of the same color purchased after some time, show color differences. Upon request, the veneered parts can be supplied with certified origin from forests managed in a correct and responsible manner, according to the rigorous environmental standards established by the FSC circuit.

### CLEANING AND MAINTENANCE

For ordinary cleaning of veneered woods, use a cloth moistened with neutral soap well diluted in water or specific products. Always dry after each application with a dry cloth or paper towel. Do not use abrasive products. In case of accidental spills of substances or liquids, immediately dab the wood with paper towel or with a dry and clean cloth. Avoid proximity to heat sources. Evenly expose the veneered woods to light, for example by periodically opening the table extensions that are stored inside the structure, or by moving any object placed on the surface, such as vases and accessories.

These tips are cleaning recommendations and do not guarantee complete stain removal.

We recommend that you always test the cleaning method on a hidden part of the item to check the resistance of the color.

Colour samples are to be considered approximate for each product. Slight color differences between a lot and the other are to be considered normal.